



<b>Article number:</b>	<b>231 226</b>			
<b>Description:</b>	<b>SITOP Solar 2000 Slave</b>			
<b>Inverter: SITOP Solar 2000 Slave</b>				
Input variables (DC)				
Recommended max. generator output	P <sub>PV</sub>	2600 W		
Max. open circuit voltage	U <sub>PV, DC</sub>	675 V		
MPP range	U <sub>PV</sub>	200 – 630 V		
Max. input voltage	I <sub>PV, max</sub>	10 A		
<b>Output values (AC)</b>				
Max. output	P <sub>AC, max</sub>	2200 W		
Power rating	P <sub>AC, B</sub>	2000 W		
Distortion factor	k	< 5 %		
Max. efficiency	η <sub>max</sub>	95 %		
European efficiency level	η <sub>euro</sub>	93.7 %		
Power consumption (operational)		< 4 W		
Power consumption (night-time operation)		0 W		
Operating temperature range	-10 °C ... +50 °C			
Relative humidity	< 95 %			
Protection rating (DIN EN 60 529)	IP21			
Size (W x H x D)	175 x 430 x 135 mm			
Weight	Approx. 5.0 kg			
Declaration of conformity	Yes			
<b>Features</b>				
<ul style="list-style-type: none"> <li>• The transformer-free technology and stable current means high yield with minimal weight.</li> <li>• No DC distribution required.</li> <li>• Integrated MPP tracker allows differing string lengths and solar generator set-ups to be implemented in a single system.</li> <li>• Multiple evaluation options through SITOP log PC visualisation software.</li> <li>• Integrated data logger for recording all major parameters.</li> <li>• No potential equalisation of module frames necessary thanks to patented switching concept.</li> </ul>				